


SABRE™ I

Satellite Broadband Communicator




The SABRE™ I brings high-speed office grade communications to your briefcase, anytime, anywhere. It is a simple to use, sub-laptop sized, fully self-contained satellite terminal. With the easy-to-carry SABRE™ I in your travel kit, you are always in touch.

FEATURES

- Simultaneous voice & data communications
- Data rate of up to 384 kbps
- Built-in Ethernet, Bluetooth and Analog Phone interfaces
- Supports voice, email, messaging, VPN, FTP, VoIP, FoIP and video media streaming
- Designed for the non-technical user
 - Swiveled antenna mount facilitates easy pointing
 - Built-in menu driven graphical user interface for use without a laptop
 - Light weight, robust and reliable
 - Wide range of accessories to meet your needs

BGAN coverage



New Generation Communications Network

The SABRE™ I enables personal broadband communications by connecting with Inmarsat's 3G compatible, Broadband Global Area Network (BGAN). BGAN is supported by the revolutionary new Inmarsat-4 satellite system.

Wireless Connectivity - Freedom to Move Around

The SABRE™ I has built-in Class 1 Bluetooth module which allows you to have wireless connectivity, up to 100m, with other Bluetooth devices such as the Bluetooth handset (SB1/BCP1000), Bluetooth headset, laptops* and PDAs*.

*Laptops and PDAs with built-in Bluetooth module or used with Bluetooth USB dongle.

Comprehensive Data and Voice Interfaces

The SABRE™ I comes with built-in Ethernet / LAN, Bluetooth and RJ11 phone interfaces. You may connect up to two of the three data interfaces at any one time.

Simultaneous Data and Voice Sessions

The SABRE™ I can simultaneously support 1 voice call and 1 data sessions.


Rugged and Easy to Use

The strong casing of the SABRE™ I allows it to withstand the toughest of environments and its swiveling hinge, makes positioning the SABRE™ I easy.

There are four ways to operate the SABRE™ I: the LCD panel on the terminal, BGAN LaunchPad or Web Console on a running laptop or Wideye Bluetooth Handset.

Best Value BGAN Terminal

The SABRE™ I is a robust, easy to use terminal offering flexible interface options. All packaged in a ready-to-go kit complete with adapters and power cords making SABRE™ I the best value BGAN terminal.



Addvalue Communications Pte Ltd, 190 Changi Road, #02-02 MDIS Building, Singapore 419974. Tel: +65 6342 5425, Fax: +65 6342 5426, Website: www.addvaluetech.com

© 2007 Addvalue Communications Pte Ltd. All rights reserved. Addvalue Communications may have pending patent applications, trademarks or registered trademarks, copyrights, or other intellectual property rights covering subject matter in this document. The furnishing of this document does not give you any license to these intellectual properties.

This material may contain unintended errors or omissions and is subject to change without notice. It is provided as is and without any express or implied warranties, including merchantability, fitness for a particular purpose and non-infringement. Addvalue shall not be liable for any special, indirect, incidental or consequential damages as a result of its use.

Addvalue, the Addvalue Enabled logo, Wideye, the Wideye logo and Sabre are either trademarks or registered trademarks of Addvalue Communications Pte Ltd in Singapore and/or other countries.

Inmarsat, the Inmarsat logo registered trademarks of Inmarsat Global Limited in the United Kingdom and/or other countries, and are used by Addvalue Communications Pte Ltd under license.

Microsoft and Windows are registered trademarks of Microsoft Corporation in the United States and/or other countries. Apple, Mac, Macintosh and Mac OS are trademarks of Apple Computer, Inc, registered in the United States and other countries. Bluetooth is a trademark of Bluetooth SIG, Inc in the United States and/or other countries. Other marks or trademarks are the properties of their respective owners.

Technical Specifications

Frequency Band
 Receive: 1525MHz - 1559MHz
 Transmit: 1626.5MHz - 1660.5MHz

Antenna
 Type: Built-in patch antenna

Bearer Data Rate
 Receive: 384 kbps (Max)
 Transmit: 240 kbps (Max)

GPS Air Interface
 Integrated GPS receiver and antenna

Streaming IP
 32 kbps, 64 kbps

Ethernet / LAN
 1 x RJ45 Ethernet Port

Phone
 1 x RJ11 Analog Phone Port

Bluetooth
 1 x Integrated access point (Ver 1.2 Class 1)

Application Support
 VPN Client, VoIP, FoIP, MPEG Streaming, Email, Messaging, Conferencing, Web Browsing.

Operating System Support
 Microsoft Windows 2000, XP, Mac OS 10.1 & above Redhat 6.0 & above

Environmental
 Operating Temp: -20°C to +60°C
 -4°F to 140°F
 Charging Temp: 0°C to +45°C
 +32°F to +113
 Operating Humidity: 95%
 (non-condensing at 40°C or +104°F)
 Storage/Humidity: 5% to 95% (RH)
 Water & Dust: IP54

Battery
 Type: Lithium ion
 Transmit Time: 1 hour continuous transmission at data rate <= 72kbps
 Receive Time: 3 hour continuous receive without transmit requirement
 Standby Time: 36 hours (typical)

Electrical
 DC Input: 10 ~ 15 Vdc (power adapter)
 12 ~ 28 Vdc (car charger)

Power Consumption
 Standby: 0.67 watts
 Operating: 22 watts (without charging)
 42 watts (with charging)

Power Adapter
 Input: 100 ~ 240 V_{AC}, 47 ~ 63 Hz
 Output: 15 V_{DC}

Weight
 1.65 Kg / 3.63 lbs

Dimensions
 259 x 195 x 58 mm
 10.10 x 7.67 x 2.28 in



For more information
 visit www.skymira.com
 or call 866.521.0540